Fresh Joint Complete Set

Technical information sheet

1 Set / Item no.006101001 / EAN 4007955061014



The white opaque renovation paint reliably refreshes greyed or damaged joints. Includes brush and special sponge for easy application. Ensures clean, even joints and a visibly renewed tile appearance - ideal for bathrooms and kitchens.

- white opaque
- resistant to washing and abrasion
- can be tinted with max. 5 % solid colour and tinting paint or with decomix universal tinting concentrate
- Complete set: 250 ml fresh grout, 1 brush, 1 special sponge

Area of application

White renovation paint for tile joints as a set with brush and special sponge.

Preparation

The tile joints must be dry and free of separating agents. Remove all soiling (e.g. soap, grease, etc.) with a scouring agent. If necessary, remove limescale deposits on the tiles with cement residue remover (check the resistance of the tiles). Roughen tile joints in older bathrooms with a joint grinder (or alternatively sandpaper).

Processing

Shake bottle well before use. Apply a generous coat of fresh grout to the joints with a brush. After one hour drying time, moisten the entire tile surface with water and wash off the colour on the tiles with a sponge. After complete drying, rub off any remaining haze with a dry cloth.

Consumption

Depending on the length and width of the joints, the contents of the pack are sufficient for approx. 20 - 30 m² of tile surface.

Storage

Keep container tightly closed and store in a cool but frost-free place.

Notes

Do not use below +5 ºC object and room temperature. Fresh grout is not suitable for unglazed tiles and for tile joints made of silicone and similar joint sealants. Not suitable for floor tiles. Only dispose of empty containers for recycling. Dried material residues can be disposed of with household waste or as construction site waste. Waste code no. EWC 08 01 12.

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.