# Woodchip Paint

Technical information sheet

5l / Item no.020456 / EAN 4016215020456
10l / Item no.020500 / EAN 4016215020500




This texturing emulsion paint creates an even, seamless woodchip look straight from the bucket. It is easy to apply, solvent-free and impresses with its good coverage. Ideal for interior wall and ceiling surfaces, it creates a modern, robust surface texture.

- White emulsion textured paint for interior wall and ceiling surfaces
- Rough fibre structure with no attachment
- Simple processing
- white opaque
- Free from solvents, plasticisers and fogging-active substances

## Area of application

Textured emulsion paint for interior wall and ceiling surfaces.

## Preparation

For all mineral substrates (such as concrete, masonry, levelling compounds, cement, gypsum and lime plaster), plasterboard and other drywall, firmly adhering emulsion paint coats as well as paintable wallpaper and wall coverings. The substrate must be dry, clean, sound, evenly absorbent and free of dust and grease. Remove loose material, old wallpaper and poorly adhering paints from the substrate. Prime highly absorbent, sanding and chalking substrates with baufan Deep Penetrating Primer LF. Repair cracks, holes and unevenness with a suitable baufan levelling compound.

## Processing

Stir well before use and apply with a roller (recommended pile thickness 16-18 mm), brush, paintbrush or suitable spraying equipment (not airless). As a primer, the paint can be diluted with max. 10 % water, as a top coat max. 5% after the first coat of paint has dried. To achieve an even texture with a roller or brush, it is recommended that the paint is applied twice in thin cross coats. When coating larger areas, work wet-on-wet to avoid build-up. Clean tools with water immediately after use. Drying time: approx. 5 hours under normal conditions (+20 °C, 65% relative humidity, moderately absorbent substrate); longer drying time under unfavourable conditions. Tinting: With universal tinting concentrates or max. 5% solid colour and tinting paint. Excess quantities will increasingly change the character of the woodchip.

## Consumption

Smooth surfaces/fine plaster grain → from 500 - 800 ml/m² Determine exact consumption quantity by test coating on the object.

## Storage

Keep container tightly closed in a cool but frost-free place. If unopened and stored properly, shelf life is at least until: see batch label.

## Notes

Processing temperature: +5 °C to +30 °C for material, circulating air and substrate Do not cover surfaces to be painted. Keep out of reach of children. Ensure adequate ventilation during application and drying. Do not inhale spray mist. Avoid eating, drinking and smoking while using the paint. Wear safety goggles. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, waterways or soil. Only dispose of empty containers for recycling. Hazardous respirable droplets may be produced when spraying. Do not inhale aerosol or mist. Use combination



Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

**Note:**
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.

filter A2/P2 when spraying.



Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

**Note:**
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.