# Latex binder

Technical information sheet




750ml / Item no.067802008 / EAN 4016215100103
2,5l / Item no.067803008 / EAN 4016215100127
5l / Item no.067804008 / EAN 4016215100141
10l / Item no.067805008 / EAN 4016215100165

Concentrated additive for refining distemper and lime paints and for reinforcing wallpaper pastes. It increases adhesion and wipe resistance, improves adhesion and forms a scrub-resistant, transparent drying coating

- for finishing distemper and lime paints
- for reinforcing wallpaper paste
- abrasion-resistant cover
- dries transparent

## Area of application

Binder for lime and distemper paints as well as wallpaper paste. Improves adhesion and wipe resistance, can also be used as a transparent coating indoors.

## Preparation

The substrate must be dry, clean, sound and free of dust and grease. Remove loose material, old wallpaper and poorly adhering paints from the substrate. Prime highly absorbent, sanding and chalking substrates with baufan Deep Primer LF. Repair cracks, holes and unevenness with a suitable baufan levelling compound.

## Processing

Additive for glue and lime paints: Reduce the amount of water required for mixing the paints by approx. 10% and replace with the corresponding amount of latex binder. Additive for wallpaper paste: Stir approx. 20% latex binder into the ready-mixed wallpaper paste. Coating for wallpaper etc.: Stir well before use and apply with a roller, brush, paintbrush or suitable spraying equipment. Use undiluted for coating wallpaper. Clean tools with water immediately after use. Not suitable for vinyl wallpapers and wallpapers with vinyl coating! Drying time: approx. 5 hours under normal conditions (+20 °C, 65% relative humidity, moderately absorbent substrate); under unfavourable conditions, the drying time will be correspondingly longer.

## Consumption

Sealer → from 150 ml/m² Glue additive → approx. 750 ml/4 ltr. glue Colour additive → approx. 1 ltr./10 ltr. colour

## Storage

Keep container tightly closed in a cool but frost-free place. If unopened and stored properly, shelf life is at least until: see batch label.

## Notes

Application temperature: +5 °C to +30 °C for material, circulating air and substrate Do not cover surfaces to be painted. Keep out of reach of children. Ensure adequate ventilation during application and drying. Do not inhale spray mist. Avoid eating, drinking and smoking while using the paint. Wear safety goggles. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, waterways or soil. Only dispose of empty containers for recycling.



Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

**Note:**
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.