Universal Wallpaper Paste

Technical information sheet

250g / Item no.160671 / EAN 4016215160671
500g / Item no.160657 / EAN 4016215160657
1kg / Item no.160633 / EAN 4016215160633



High-quality, synthetic resin-reinforced wallpaper adhesive for light to normal paper wallpapers as well as heavy wallpapers and non-woven wallpapers. The high-yield, strong adhesive formula ensures reliable adhesion and clean application. The low-dust granules are odourless, ready to use quickly and dry stain-free - ideal for precise and professional wallpapering work.

- for vinyl and textured wallpapers, embossed and other heavy wallpapers
- for non-woven wallpaper
- Ready to use in 5 minutes
- with polymer adhesive booster

Area of application

Wallpaper paste for paper, heavy wallpapers and non-woven wallpapers. Strong adhesive, economical, odourless and low-dust for clean results.

Preparation

For optimum adhesion, the substrate must be dry, stable and free of dust and grease. Remove old, poorly adhering wallpaper and loose coats of paint with baufan wallpaper stripper. Repair cracks and holes. Pre-treat highly absorbent substrates with baufan Deep Penetrating Primer LF.

Processing

Add baufan Universal Wallpaper Adhesive quickly and rapidly to cold, clean water while stirring vigorously and continue stirring for a short time. (Depending on the wallpaper: 5 litres for heavy wallpapers, 7.5 litres for light wallpapers) After 5 minutes, stir again vigorously. Paste the wallpapers evenly and lay them together. After sufficient soaking time, apply butt joints. For non-woven wallpapers, it is sufficient to apply the paste to the wall with a roller and then apply the wallpaper directly from the roll. The instructions of the wallpaper manufacturer must be followed. Dab off any paste residue with a clean, damp cloth. Clean tools with water after use. Mixing ratio: Pre-pasting: Mix 1:40 = 10 litres of water = 50-55 m² Heavy wallpapers and non-woven wallpapers: Mix 1:20 = 5 litres of water = 25-30 m² Paper wallpapers: Mix 1:30 = 7.5 litres of water = 35-40 m²

Storage

Keep container tightly closed in a cool but frost-free place. When unopened and stored properly, at least 60 months.

Notes

Waste code no. 080410 (waste adhesives and sealants). Only dispose of empty containers for recycling. Material residues can be disposed of as powder or dried according to waste code no. 170904 (mixed construction and demolition waste) or as household waste.

Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

Note:
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.