



Colourless, non-yellowing acrylate-based protective coating for wallpapers, white and coloured emulsion paints, decorative wall glaze and filler techniques, bricks, natural and artificial stone masonry, posters, collages, maps and similar interior surfaces.

- Colourless protective coating for heavily used interior surfaces
- Dirt and water repellent
- For wallpapers, white and coloured emulsion paints, decorative wall glaze and filler techniques and similar substrates
- acrylate-based
- solvent-free
- resistant to washing and abrasion

Area of application

Colourless, acrylate-based protective coating for wallpaper, emulsion paints and stone. Non-yellowing, washable and ideal for kitchens, hallways and children's rooms.

Preparation

The substrate must be dry, clean, sound, evenly absorbent and free of dust and grease.

Processing

baufan wallpaper protection is ready to use and can be applied with a brush or suitable spraying equipment. The gloss level of the coating depends on the surface structure of the substrate. In order to achieve an even, glossy coating, two coats are therefore required for rough substrates. For semi-gloss surfaces, baufan Wallpaper Protection can be diluted 1:1 with water. baufan Wallpaper Protection can be diluted up to 1:4 with water, depending on the absorbency of the substrate. Protect components that are not to be treated from splashes - e.g. by covering them - as dried wallpaper protection is difficult to remove. Do not apply below + 5° Celsius substrate and room temperature! Clean tools with water immediately after use.

Storage

Keep container tightly closed in a cool but frost-free place. If unopened and stored properly, shelf life is at least until: see batch label.

Notes

Processing temperature: +5 °C to +30 °C for material, ambient air and substrate Keep out of reach of children. Ensure adequate ventilation during application and drying. Avoid eating, drinking and smoking during use. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, waterways or soil. Only dispose of empty containers for recycling.

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.