# Wallpaper Power Remover

Technical information sheet

1l / Item no.102299 / EAN 4016215102299




Extra strong woodchip stripper in master quality for the effortless removal of multi-coated woodchip and other difficult-to-remove wallpapers. The highly effective formula penetrates deep into the layers, removes even stubborn adhesions quickly and reliably and saves time during renovation work. Very economical, easy to apply with a brush and ideal for indoor use - for clean surfaces and optimum preparation of new wall designs.

- Ideal for painted woodchip and heavy wallpaper
- Extra strong dissolving power and extremely high penetrating ability
- Quick soaking of the wallpaper

## Area of application

Rough wallpaper stripper for paper, textile and vinyl wallpapers as well as distemper. Also removes painted woodchip quickly, thoroughly and reliably indoors.

## Preparation

For paper, textile and vinyl wallpapers as well as distemper coatings.

## Processing

Stir 250 ml baufan Rauhfaser-Kraftlöser into 5 litres of water. For light wallpapers, the amount of water added can be increased to 10.0 litres. Dilute larger quantities in the appropriate ratio. Hot water increases the effect. Apply the solution generously with a brush or a suitable sprayer (do not inhale the spray mist) and leave to work for approx. 15 minutes. Repeat the application if necessary. The soaked wallpaper can then be easily removed. Roughen water-resistant and painted wallpaper with a needle roller or coarse sandpaper before treatment. To remove distemper coatings, apply baufan Rauhfaser Kraftlöser (dilution 1:60) to the surface and remove with a scraper after a short exposure time. Remove any residue by washing off. The fibre remover is neutral. Stains can be easily removed with water. Subsequent bonding is not affected. Clean tools with water.

## Consumption

1.0 litre is sufficient for approx. 150 - 200 m2 (depending on dilution)

## Storage

Keep container tightly closed in a cool but frost-free place. If unopened and stored properly, shelf life is at least until: see batch label.

## Notes

Processing temperature: +5 °C to +30 °C for material, circulating air and substrate Important information: Keep out of reach of children. Ensure adequate ventilation during application. Do not inhale spray mist. Avoid eating, drinking and smoking during use. Avoid contact with eyes and skin. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not allow to enter drains, waterways or soil. Only dispose of empty containers for recycling.



Baufan Bauchemie Leipzig GmbH ■ Ludwig-Hupfeld-Straße 19 ■ 04178 Leipzig ■ Telephone +49 (0)341 44655-0 ■ Email info@baufan.de ■ www.baufan.com

**Note:**
All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.